

Reminder

#2010

CM # 14

EXAMPLE 5.10
Strength of
Column with
Slender Elements

Goal: Determine the available strength of a compression member with a slender web.

Given: Use a W16x26 as a column with $L_{cy} = 5.0$ ft.

Solution:

①

check column whether \rightarrow Elastic
 \rightarrow inelastic


$A992_{steel} \Rightarrow F_y = 50 \text{ ksi}$

$$\frac{KL}{r} \Rightarrow \text{or } \frac{L_e}{r} = 4.71 \sqrt{E/F_y} = 4.71 \sqrt{\frac{29000}{50}} = 113.43$$

From Table 1-1 For W16x26

$$L_{cy} = 5.00 \text{ FT} \quad r_y = 1.12 \text{ inch}^3$$

$$\left(\frac{KL}{r}\right)_y \Rightarrow \frac{L_{cy}}{r_y} = \frac{5(12)}{1.12} = 53.57 \Rightarrow \text{inelastic}$$



Prepared by Eng. Maged Kamel.


< 113.43

(a) For uniformly compressed slender elements, with $\frac{b}{t} \geq 1.49 \sqrt{\frac{E}{f}}$, except flanges of square and rectangular sections of uniform thickness:

$$b_e = 1.92t \sqrt{\frac{E}{f}} \left[1 - \frac{0.34}{(b/t)} \sqrt{\frac{E}{f}} \right] \leq b \quad (\text{E7-17})$$

$$F_E = \frac{\pi^2 E}{\left(\frac{KL}{r}\right)^2} = \frac{\pi^2 (29000)}{(53.57)^2} = 99.73 \text{ ksi}$$

$$\lambda_c^2 = \frac{F_y}{F_E} = \frac{50}{99.73} = 0.501$$



Prepared by Eng. Maged Kamel.

From previous pos²

(a) For uniformly compressed slender elements, with $\frac{b}{t} \geq 1.49 \sqrt{\frac{E}{f}}$, except flanges of square and rectangular sections of uniform thickness:

$A_g =$

$Q = 1$


$$b_e = 1.92t \sqrt{\frac{E}{f}} \left[1 - \frac{0.34}{(b/t)} \sqrt{\frac{E}{f}} \right] \leq b \quad (E7-17)$$

$\lambda_c < 2.25$
 $F_{cr} = 0.658^{\lambda_c^2} F_y$
 $= 0.658^{(0.50)^2} (50)$

$f_{cr} = 40.54 \text{ ksi}$

$\phi P_n = 280 \text{ kips}$

$P_n / \Omega = 187 \text{ kips}$



Prepared by Eng. Maged Kamel.

In the previous post \rightarrow post 16

$$\phi = 1$$

$$r^2 = 0.501$$

But we will use ϕ_{new}

$$A_e = 6.83 \text{ inch}^2$$

$$A_g = 7.68 \text{ inch}^2$$


$$\phi = \frac{A_e}{A_g} = \frac{6.83}{7.68} = 0.889$$

$$\text{New } F_{cr} = 0.658 \quad (F_y \phi)$$

$$(0.889)(50)$$

$$F_{cr} = 0.658 \quad (50)(0.889)$$

$$= 36.92 \text{ ksi}$$



For $\phi = 0.889$

$f_{cr} = 36.92 \text{ ksi}$

$$A_g = 7.68 \text{ inch}^2$$

$$A_{eff} = 6.83 \text{ inch}^2$$

$$P_n = A_g f_{cr} = 7.68 (36.92) = 283.55$$


$$\phi P_n = 0.9 (284) = 256 \text{ kips}$$

$$\frac{P_n}{\phi} = \frac{284}{1.67} = 170 \text{ kips}$$

(a) For uniformly compressed slender elements, with $\frac{b}{t} \geq 1.49 \sqrt{\frac{E}{f}}$, except flanges of square and rectangular sections of uniform thickness:

Get new k_e

$$b_e = 1.92t \sqrt{\frac{E}{f}} \left[1 - \frac{0.34}{(b/t)} \sqrt{\frac{E}{f}} \right] \leq b \quad (E7-17)$$



$$k_{des} = 0.747''$$

$$E = 29000 \text{ ksi}$$

$$t = t_{web}$$

$$f = f_{cr} = 36.92 \text{ ksi}$$

$$\frac{b}{t} = \frac{h_w}{t_w}$$

$$\text{Find } h_w = d - 2k_{des}$$

$$= 15.7 - 2(0.747)$$

$$h_w = 14.21''$$

$$\frac{b}{t} = \frac{14.21}{0.25} = 56.80$$


(a) For uniformly compressed slender elements, with $\frac{b}{t} \geq 1.49 \sqrt{\frac{E}{f}}$, except flanges of square and rectangular sections of uniform thickness:

$$F_{cr} = 36.92 \text{ ksi}; \quad b_e = 1.92t \sqrt{\frac{E}{f}} \left[1 - \frac{0.34}{(b/t)} \sqrt{\frac{E}{f}} \right] \leq b \quad (\text{E7-17})$$

$$h_e = b_e = 1.92 (0.25) \sqrt{\frac{29000}{36.92}} \left[1 - \frac{0.34}{56.8} \sqrt{\frac{29000}{36.92}} \right]$$

$$h_e = b_e = 11.20'' < 14.21''$$

d - 2 kdes



Find A_{eff} web

Flange is fully active
 $\lambda_F < \lambda_r$

Effective web
 area

$$h_w = 14.21''$$

$$t_w = 0.25''$$

$$h_e = 11.20''$$

$$t_w = 0.25'' \Rightarrow A_{ef} = 11.2(0.25)$$

$$= 2.80 \text{ inch}^2$$

$$A_w = 3.55 \text{ inch}^2$$

reduced \rightarrow

$$A_{sect} = A_g - (h_w)(t_w) + A_{ef} w$$

$$A_e = 7.68 - 3.55 + 2.8 = 6.93 \text{ inch}^2$$

$$A_e = 6.93 \text{ inch}^2$$

$$A_g = 7.68 \text{ inch}^2$$

$$Q = \frac{A_e}{A_g} = \frac{6.53}{7.68} = 0.902$$

$$\approx 0.90$$

$$F_{cr} = 0.658 (0.45) (50) (0.9)$$

$$= 37.27$$

$$\lambda_c^2 = \frac{F_y}{F_E} = \frac{50}{99.73} = 0.5$$

$$Q \lambda_c^2 = 0.9 (0.5)$$

$$= 0.45$$


Ksi

LRFD: $0.9 (7.68) (37.27)$

$$= \underline{258 \text{ kips}}$$

ASD: $\frac{7.68 (37.27)}{1.67}$

$$= 171 \text{ kips}$$



DESIGN TABLE DISCUSSION

Table 6-1. W-Shapes in Combined Flexure and Axial Force

Steel W-shapes with $F_y = 50$ ksi (ASTM A992) and subject to combined axial force (tension or compression) and flexure may be checked for compliance with the provisions of Section H1.1 and H1.2 of the AISC *Specification* using values listed in Table 6-1 and the appropriate interaction equations provided in the following sections.

Values p , b_x , b_y , t_y and t_r presented in Table 6-1 are defined as follows.

	LRFD	ASD
Axial Compression	$p = \frac{1}{\phi_c P_n}, (\text{kips})^{-1}$	$p = \frac{\Omega_c}{P_n}, (\text{kips})^{-1}$

$$\phi_c P_n = \frac{1000}{p}$$
$$\frac{P_n}{\Omega} = \frac{1000}{p}$$

COMPOSITE MEMBERS SUBJECT TO COMBINED FLEXURE AND AXIAL COMPRESSION

For the design of composite members subject to combined flexure and axial compression, see *AISC Specification* Section I5.

DESIGN TABLE DISCUSSION

Table 6-1. W-Shapes in Combined Flexure and Axial Force

Steel W-shapes with $F_y = 50$ ksi (ASTM A992) and subject to combined axial force (tension or compression) and flexure may be checked for compliance with the provisions of Section H1.1 and H1.2 of the *AISC Specification* using values listed in Table 6-1 and the appropriate interaction equations provided in the following sections.

Values p , b_x , b_y , t_y and t_r presented in Table 6-1 are defined as follows.

	LRFD	ASD
Axial Compression	$p = \frac{1}{\phi_c P_n}, (\text{kips})^{-1}$	$p = \frac{\Omega_c}{P_n}, (\text{kips})^{-1}$
Strong Axis Bending	$b_x = \frac{8}{9\phi_b M_{nx}}, (\text{kip-ft})^{-1}$	$b_x = \frac{8\Omega_b}{9M_{nx}}, (\text{kip-ft})^{-1}$
Weak Axis Bending	$b_y = \frac{8}{9\phi_b M_{ny}}, (\text{kip-ft})^{-1}$	$b_y = \frac{8\Omega_b}{9M_{ny}}, (\text{kip-ft})^{-1}$
Tension Yielding	$t_y = \frac{1}{\phi_t F_y A_g}, (\text{kips})^{-1}$	$t_y = \frac{\Omega_t}{F_y A_g}, (\text{kips})^{-1}$
Tension Rupture	$t_r = \frac{1}{\phi_t F_u (0.75 A_g)}, (\text{kips})^{-1}$	$t_r = \frac{\Omega_t}{F_u (0.75 A_g)}, (\text{kips})^{-1}$

$$\phi_c P_n = \frac{1000}{3.37} = 297 \text{ kips at } l_c = 0$$

AISC-360-10

6-62

DESIGN OF MEMBERS SUBJECT TO COMBINED FORCES

CM #14



W16x26

L = 5' W-Shapes



Table 6-1 (continued)
Combined Flexure
and Axial Force

$F_y = 50$ ksi

Shape		W16x							
		31 ^c				26 ^{c, v}			
Design		$p \times 10^3$ (kips) ⁻¹		$b_x \times 10^3$ (kip-ft) ⁻¹		$p \times 10^3$ (kips) ⁻¹		$b_x \times 10^3$ (kip-ft) ⁻¹	
		ASD	LRFD	ASD	LRFD	ASD	LRFD	ASD	LRFD
with respect to least radius of gyration, r_y length, L_y (ft), for X-X axis bending	0	4.09	2.72	6.60	4.39	5.06	3.37	8.06	5.36
	6	5.08	3.38	7.28	4.85	6.33	4.21	9.07	6.03
	7	5.52	3.67	7.71	5.13	6.91	4.60	9.66	6.43
	8	6.10	4.06	8.19	5.45	7.68	5.11	10.3	6.87
	9	6.87	4.57	8.74	5.82	8.70	5.79	11.1	7.39
	10	7.89	5.25	9.37	6.23	10.1	6.72	12.0	7.99
	11	9.28	6.17	10.1	6.71	12.0	8.01	13.1	8.69
	12	11.0	7.34	11.1	7.35	14.3	9.53	15.0	10.0
	13	13.0	8.62	12.6	8.39	16.8	11.2	17.2	11.5
	14	15.0	10.0	14.2	9.45	19.5	13.0	19.5	13.0
	15	17.2	11.5	15.8	10.5	22.4	14.9	21.9	14.6
	16	19.6	13.1	17.5	11.6	25.5	16.9	24.3	16.2
	17	22.2	14.7	19.2	12.8	28.7	19.1	26.7	17.8
	18	24.8	16.5	20.9	13.9	32.2	21.4	29.2	19.4
	19	27.7	18.4	22.6	15.0				

by
Estimate
LRFD
 $L_{cy} = 5'$
2SB
Kips

$$\phi_c P_n = \frac{1000}{4.21} = 237.5 \text{ kips at } L_y = 6'$$

$$\frac{P_n}{A} = \frac{1000}{5.06} = 197.60 \text{ kips} \approx 198 \text{ kips} \quad L_y = 0'$$

DESIGN OF MEMBERS SUBJECT TO COMBINED FORCES

Shape		W16x							
		31 ^c				26 ^{c, v}			
Design		$p \times 10^3$ (kips) ⁻¹		$b_x \times 10^3$ (kip-ft) ⁻¹		$p \times 10^3$ (kips) ⁻¹		$b_x \times 10^3$ (kip-ft) ⁻¹	
		ASD	LRFD	ASD	LRFD	ASD	LRFD	ASD	LRFD
	0	4.09	2.72	6.60	4.39	5.06	3.37	8.06	5.36
	6	5.08	3.38	7.28	4.85	6.33	4.21	9.07	6.03
	7	5.52	3.67	7.71	5.13	6.91	4.60	9.66	6.43
	8	6.10	4.06	8.19	5.45	7.68	5.11	10.3	6.87
	9	6.87	4.57	8.74	5.82	8.70	5.79	11.1	7.39
	10	7.89	5.25	9.37	6.23	10.1	6.72	12.0	7.99
	11	9.28	6.17	10.1	6.71	12.0	8.01	13.1	8.69
	12	11.0	7.34	11.1	7.35	14.3	9.53	15.0	10.0
	13	13.0	8.62	12.6	8.39	16.8	11.2	17.2	11.5
	14	15.0	10.0	14.2	9.45	19.5	13.0	19.5	13.0
	15	17.2	11.5	15.8	10.5	22.4	14.9	21.9	14.6
	16	19.6	13.1	17.5	11.6	25.5	16.9	24.3	16.2
	17	22.2	14.7	19.2	12.8	28.7	19.1	26.7	17.8
	18	24.8	16.5	20.9	13.9	32.2	21.4	29.2	19.4
	19	27.7	18.4	22.6	15.0				

ASD
 $L_y = 5'$
 171
 → kips

$$\frac{P_n}{A} = \frac{1000}{6.33} = 158 \text{ kips} \quad L_y \approx 6 \text{ FT}$$