

Using the given sections, all of A992 steel, and the plastic theory, determine the values of  $P_n$  and  $w_n$  as indicated.

Solution

A992 steel




FIGURE P8-33

section W16 x 26  
Find  $M_n$

$$\left[ \begin{array}{l} Z_x = 44.20 \text{ in}^3 \\ F_y = 50 \text{ ksi} \\ M_p = F_y Z_x = 50 \text{ k} \frac{\text{lb}}{\text{inch}^2} (44.20) \text{ inch}^3 \end{array} \right.$$

$$M_n = M_p = 2210 \text{ Kips} \cdot \text{inch}$$

Prepared by Eng. Maged Kamel. or  $= \frac{2210}{12} = 184.167 \text{ kips} \cdot \text{FT}$

A992 steel

Shape	Steel Type		
	ASTM Designation	$F_y$ , ksi	$F_u$ , ksi
Wide flanged beams	A992	50-65	65
Miscellaneous beams	A36	36	58-80
Standard beams	A36	36	58-80
Bearing piles	A572 Gr. 50	50	65
Standard channels	A36	36	58-80
Miscellaneous channels	A36	36	58-80
Angles	A36	36	58-80
Ts cut from W-shapes	A992	50-65	65
Ts cut from M-shapes	A36	36	58-80
Ts cut from S-shapes	A36	36	58-80
Hollow structural sections, rectangular	A500 Gr. B	46	58
Hollow structural sections, square	A500 Gr. B	46	58
Hollow structural sections, round	A500 Gr. B	42	58
Pipe	A53 Gr. B	35	60

Note:  $F_y$  = specified minimum yield stress;  $F_u$  = specified minimum tensile strength



W-Shapes



M-Shapes



S-Shapes



HP-Shapes



C-Shapes



L-Shapes



WT-Shapes



ST-Shapes



HSS-Shapes



Pipe

Prepared by Eng.Maged Kamel.

**8.83**

Using the given sections, all of A992 steel, and the plastic theory, determine the values of  $P_n$  and  $w_n$  as indicated.




FIGURE P8-33

ID: Number of Indeterminacy

$$= 4 - 2 = 2$$

$\sum Y = 0$   
 $\sum M = 0$

Except HL loads

$$ID = (2m + r) - 2n$$

$$= 2(3) + 4 - 2(4) = 2$$

Same result

Possible hinge Locations:  $B', B, C', C, D' = 5$

Number of Mechanism =  $5 - 2 = 3$

A	B'	B	Same
B	B'	C	
C	D'	D	




FIGURE P8-33

Possible Mechanisms


Real hinge

1st Mechanism  
3 real plastic hinges

2nd Mechanism

Real hinge  
3rd mechanism

Same results






FIGURE P8-33


First panel  $L \Rightarrow 2$  P. Hings  
3rd

Derive the expression  
For  $x$  distance


For shear = 0

$$dM/dx = 0$$

First panel



$M_p$



$$R_A = 2w_n \left( \frac{L}{2} \right) - \frac{M_p}{L}$$

For  $Q = 0 \Rightarrow w_n L - \frac{M_p}{L} = 2w_n (x)$

$$\frac{M_p}{L} = w_n L - 2w_n x \Rightarrow \text{Expression for } M_p$$

$$L M_p = w_n L^2 - 2w_n x L$$

For  $M_x = M_p$  L.H.S  $\Rightarrow w_n Lx - \frac{M_p}{L}(x) - w_n x^2$   
R.H.S  $\Rightarrow M_p$






FIGURE P8-33

Continue First and third  
Derive the expression  
For x distance  
For shear = 0

First panel



$$w_n Lx - Mp\left(\frac{x}{L}\right) - w_n x^2 = Mp$$

$$Mp + Mp\left(\frac{x}{L}\right) = -w_n x^2 + w_n Lx \rightarrow \text{but } Mp = w_n l^2 - 2w_n xL$$

$$w_n l^2 - 2w_n xL + w_n Lx - 2w_n x^2 = -w_n x^2 + w_n Lx$$

$$w_n x^2 + 2w_n xL - w_n l^2 = 0$$

$$x^2 + 2xL + L^2 = 0$$

Divide  
 $\frac{\quad}{w_n}$

$$x = \frac{-2 \pm \sqrt{4 + 4}}{2} = 0.414 L$$





FIGURE P8-33

First & Third span

Derive the expression  
For x distance  
For shear = 0

First panel



Back to the expression  
For shear, put  $x =$

$$0.414 L$$

$$w_n L - 2w_n x - \frac{M_p}{L} = 0$$

$$w_n \ell - \frac{184.167}{L} - 2w_n (0.414 L) = 0$$

$$M_p = 184.167 \text{ Ft. kips}$$

$$\ell = 16'$$

$$\frac{43}{250} w_n L = \frac{184.167}{L} \Rightarrow w_n = \frac{184.167 (250)}{(16)^2 \cdot 43} = 4.193 \text{ kips/ft}$$

Prepared by Eng. Maged Kamel.







FIGURE P8-33

W16 x 26

$M_p = 184.167$   
FT. kips

First span or third span



External work =  $w_n L \frac{\Delta}{2}$


internal work =  $M_p (\theta_1 + \theta_2 + \theta_2)$

$w_n L \Delta = M_p (5.8284) \Delta \Rightarrow l = 16m$   
 $M_p = 184.167$

$\theta_1 = \frac{\Delta}{0.414L}$   
 $\theta_2 = \frac{\Delta}{0.586L}$   
 $\theta_1 + \theta_2 = \frac{4.1219}{L} \Delta$   
 $\theta_2 = \frac{1.7065}{L} \Delta$

$w_n = \frac{(184.167)(5.8284)}{(16)^2}$   
 $= 4.193 \text{ K/F}$

Prepared by Eng. Maged Kamel.



Static method


W16 x 26

FT. kip's

$$M_p = 184.167$$

FIGURE P8-33

2nd span 3 free plastic hinges



External work =  $\frac{w_n L}{2} \frac{\Delta}{2} (2) = w_n L \frac{\Delta}{2}$   
 internal work

$$= M_p (\theta + \theta + 2\theta) = 4 M_p (\theta) = M_p \frac{8\Delta}{L}$$


$$\theta = \frac{\Delta}{L/2}$$

$$w_n L \frac{\Delta}{2} = 8 M_p \frac{\Delta}{L}$$

$$4\theta = \frac{8\Delta}{L}$$

$$w_n = \frac{16 M_p}{L^2} = \frac{16 (184.167)}{(16)^2} = 11.510 \text{ kip/ft}$$

$$w_n = \min(4.193, 11.510) = 4.193 \text{ kip/ft}$$





$M_p = 184.167$   
FT. kips

FIGURE P8-33

$184.167$   $184.167$   $184.167$

Check  $2M_p = \frac{w_n L^2}{8}$




$4.193 \frac{(16)^2}{8}$   
 $= 134.176$

$67.088$   
 $11.510$   

---


 $55.578$

$55.578(6.624) - \frac{8.386(6.624)^2}{2}$   
 $= M_p = 184.17$   
FT. kips



$$W_w = 0.20 \text{ k/inch} \quad \lambda = 1.747 \Rightarrow 0.3494 \frac{\text{k}}{\text{inch}} \rightarrow 4.1928 \frac{\text{k}}{\text{FT}} \text{ Same}$$

\*\*\*\* Deflected Shape: 1<sup>st</sup>-Order Inelastic, Incr # 18, Applied Load Ratio = 1.7472 \*\*\*\*



$$\left. \begin{array}{l} F_y = 50 \text{ ksi} \\ E = 29000 \text{ ksi} \end{array} \right\} \begin{array}{l} \text{Nominal Load} \\ \text{Four plastic hinges} \end{array} \quad \begin{array}{l} \lambda_1 = 1.661 (0.20) = 0.3322 \\ \lambda_2 = 1.747 (0.2) = 0.3494 \end{array} \frac{\text{k}}{\text{inch}}$$


7.9728 k/F

First hinge


at  $w_n = 0.3322$  k/inch

First panel = 0.6644 k/inch

Load  $\Rightarrow = 7.9728 \frac{k}{F}$



$$M_p = 54.215(6.624) - 7.9728 \frac{(6.624)^2}{2} = 184.20 \text{ Ft-kips}$$




Two plastic hinges


4

$$M_Z = M_n = 2210 \text{ inch. kip} = M_n = F_Z z_x$$

MASTAN.2



There is no hinge in the mid of span - 2



Shear diagram

